

Rubber-like look and feel enhances flexibility while maintaining durability and cost efficiencies of PVC.

#### POTENTIAL USE:

- Multipurpose applications
- Air & water (up to 150° F)
- Pneumatic tools
- Air service for painting equipment
- Coolant lines

#### FEATURES:

- U.V. & Ozone Resistant
- Non-Marking Cover
- Lightweight
- Long continuous lengths
- Silicone free tube & cover
- Chemical resistance of PVC
- Meets RMA (Class B) oil resistance

#### CONSTRUCTION:

- **Tube:** Specially Formulated, PVC Compound
- **Reinforcement:** High Tensile Strength Textile Cord
- **Cover:** Specially Formulated, PVC Compound



**TEMPERATURE:** -15° F (-26° C) to +150° F (+65° C) continuous service

**BRANDING:** Flex-Tech RT Multi-Purpose - 3/8" ID 300 PSI W.P. (2.1 Mpa) Made in USA

| Part#          | I.D. | O.D.  | Max W.P. | Wt/ft. | Length | Type     | End Conn.  |
|----------------|------|-------|----------|--------|--------|----------|------------|
| RT-0250XX-RL   | 1/4" | 0.5   | 300 psi  | 0.095  | 500 ft | Reel     | none       |
| ART0250XX25MM  | 1/4" | 0.5   | 300 psi  | 0.095  | 25 ft  | Assembly | MNPT       |
| ART0250XX50MM  | 1/4" | 0.5   | 300 psi  | 0.095  | 50 ft  | Assembly | MNPT       |
| ART0250XX100MM | 1/4" | 0.5   | 300 psi  | 0.095  | 100 ft | Assembly | MNPT       |
| ART0250XX25QP  | 1/4" | 0.5   | 300 psi  | 0.095  | 25 ft  | Assembly | Quick/Plug |
| ART0250XX50QP  | 1/4" | 0.5   | 300 psi  | 0.095  | 50 ft  | Assembly | Quick/Plug |
| ART0250XX100QP | 1/4" | 0.5   | 300 psi  | 0.095  | 100 ft | Assembly | Quick/Plug |
| RT-0375XX-RL   | 3/8" | 0.595 | 300 psi  | 0.105  | 500 ft | Reel     | none       |
| ART0375XX25MM  | 3/8" | 0.595 | 300 psi  | 0.105  | 25 ft  | Assembly | MNPT       |
| ART0375XX50MM  | 3/8" | 0.595 | 300 psi  | 0.105  | 50 ft  | Assembly | MNPT       |
| ART0375XX100MM | 3/8" | 0.595 | 300 psi  | 0.105  | 100 ft | Assembly | MNPT       |
| ART0375XX25QP  | 3/8" | 0.595 | 300 psi  | 0.105  | 25 ft  | Assembly | Quick/Plug |
| ART0375XX50QP  | 3/8" | 0.595 | 300 psi  | 0.105  | 50 ft  | Assembly | Quick/Plug |
| ART0375XX100QP | 3/8" | 0.595 | 300 psi  | 0.105  | 100 ft | Assembly | Quick/Plug |
| RT-0500XX-RL   | 1/2" | 0.785 | 300 psi  | 0.132  | 500 ft | Reel     | none       |
| ART0500XX25MM  | 1/2" | 0.785 | 300 psi  | 0.132  | 25 ft  | Assembly | MNPT       |
| ART0500XX50MM  | 1/2" | 0.785 | 300 psi  | 0.132  | 50 ft  | Assembly | MNPT       |
| ART0500XX100MM | 1/2" | 0.785 | 300 psi  | 0.132  | 100 ft | Assembly | MNPT       |
| RT-0625XX-RL   | 5/8" | 0.915 | 300 psi  | 0.185  | 500 ft | Reel     | none       |
| RT-0625XX-50   | 5/8" | 0.915 | 300 psi  | 0.185  | 50 ft  | Coil     | none       |
| RT-0625XX-100  | 5/8" | 0.915 | 300 psi  | 0.185  | 100 ft | Coil     | none       |
| RT-0750XX-RL   | 3/4" | 1.07  | 300 psi  | 0.29   | 600 ft | Reel     | none       |
| RT-0750XX-50   | 3/4" | 1.07  | 300 psi  | 0.29   | 50 ft  | Coil     | none       |
| RT-0750XX-100  | 3/4" | 1.07  | 300 psi  | 0.29   | 100 ft | Coil     | none       |
| RT-1000XX-RL   | 1"   | 1.44  | 200 psi  | 0.45   | 400 ft | Reel     | none       |
| RT-1000XX-50   | 1"   | 1.44  | 200 psi  | 0.45   | 50 ft  | Coil     | none       |
| RT-1000XX-100  | 1"   | 1.44  | 200 psi  | 0.45   | 100 ft | Coil     | none       |

\* 300 PSI (2.1 Mpa) at 70 F (21 C), 250 PSI (.72 Mpa) at 150 F (+66 C).

\* Weight Per Foot does not include fittings.

\* **Strain Relief(s) / Bend Restrictor(s)** are available and may be added to assemblies at a Net (\$) increase per assembly

#### TO PLACE AN ORDER:

Use the above **Item Number** and appropriate letters for **color** choice in the blank space

Indicated by XX. **EX:** A reel of 3/8" Flex **RT** with **Red** cover would be ordered as: **RT-0375RD-RL**

**RD = Red, GR = Green, BL = Blue, YW = Yellow, BK = Black**