

Flexible reinforced PVC kink-resistant hose manufactured from carefully selected, materials that comply with IAPMO TS-25, FDA & NSF/ANSI-61.

POTENTIAL USE:

- RV cold water, plumbing, & marine connections
- Cold water transfer
- Drinking water plumbing
- Deionized water
- Cold water manifold connection
- Potable water delivery pump connections
- Cold water risers
- Light-duty washdown



FEATURES:

- Tube made from NSF/ANSI-61 listed materials for water contact.
- Hose conforms to IAPMO to TS-25, Standard for Reinforced Hose for use in Recreational Vehicle Pressurized Cold Water Systems.
- Water contact materials contain no substances designated as hazardous under California Proposition 65
- When coupled properly, hose will pass IAPMO proof test requirement of 300 psi at 73°F for 48 hours
- Lightweight with superior flexibility

CONSTRUCTION:

- **Tube:** White ANSI/NSF Standard 61 Listed PVC, formulate din compliance with FDA & California Prop 65 non-toxic drinking water safe
- **Reinforcement:** High tensile strength synthetic yarn
- **Cover:** Unfilled (clear) high molecular weight clear PVC formulated for excellent U.V. resistance and weather aging.

TEMPERATURE: 25° F (-4° C) to 125° F (52° C) continuous service

Part#	I.D.	O.D.	Max W.P.	Wt./ft	Lengths
MRV-06CW-00	3/8"	0.575	150 psi	0.075	500 ft
MRV-08CW-00	1/2"	0.695	150 psi	0.100	500 ft
MRV-10CW-00	5/8"	0.845	150 psi	0.145	300 ft